

Proudly Australian Made

## 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

**Product Name:** Omega Crack Injection Epoxy Part B

**Recommended Uses:** A two pack epoxy coating. Applied by roller or brush. Also refer to the SDS for part A

**Supplier:** Omega International Coatings P/L

**Street Address** 111, Kurrajong Ave, Mount Druitt, NSW, 2770

**Telephone Number:** (02) 9832 0000

**E mail:** info@omegapaints.com.au

**Emergency Telephone Number** **Australia: 1800 033 111** **New Zealand: 0800 734 607**

## 2. HAZARDS IDENTIFICATION

This material is Corrosive according to health criteria of Safe Work Australia.



### Hazard Classification

Acute Toxicity- Dermal -Category 4

Acute Toxicity -Inhalation – Category 4

Skin Corrosion/irritation – Category 2

Serious eye damage/ irritation – Category 2A

Sensitization-Skin-Category 1

Specific Target Organ Toxicity (Single Exposure) – Category 3

### Hazard Statement(s)

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

### Prevention Precautionary Statement(s)

P102 Keep out of reach of children

P103 Read label before use

## Proudly Australian Made

|      |   |
|------|---|
| P210 | Keep away from all source of ignition- No smoking   |
| P233 | Keep container tightly closed   |
| P240 | Ground/bond container and receiving equipment   |
| P241 | Use explosion-proof electrical, ventilating, lighting and all other equipment             |
| P242 | Using only non-sparking tools   |
| P243 | Take precautionary measures against static discharge                                      |
| P261 | Avoid breathing mist, vapor or spray  |
| P271 | Use only outdoors or in a well-ventilated area  |
| P272 | Contaminated work clothing should not be allowed out of the workplace                     |
| P280 | Wear protective clothing, gloves, eye/face protection and suitable respirator as required |

### Response Precautionary Statement (s)

|              |   |
|--------------|---|
| P101         | If medical advice is needed, have product container or label at hand                                      |
| P302+352     | IF ON SKIN: Wash with soap and water  |
| P303+361+353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower |
| P304+340     | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.          |
| P312         | Call a POISON CENTRE or doctor/physician if you feel unwell   |
| P363         | Wash contaminated clothing before reuse   |
| P333+313     | If skin irritation or a rash occurs: Get medical advice/attention   |
| P370+378     | In case of fire: Use alcohol resistance foam for extinction   |

### Storage Precautionary Statement(s)

|          |   |
|----------|---|
| P405     | Store locked up                           |
| P403+235 | Store in well ventilated place. Keep cool |

### Disposal Precautionary Statement(s)

|      |  |
|------|--|
| P501 | Dispose of contents/container in accordance with local, regional, national and international regulations Poisons Schedule (Aust): S5 |
|------|--|

## DANGEROUS GOODS CLASSIFICATION

Not Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

## 3. COMPOSITION INFORMATION

| Chemical Entity | CAS No. | Proportion (%w/w) |
|-----------------|---------|-------------------|
|-----------------|---------|-------------------|

Proudly Australian Made

|  |           |        |
|--|-----------|--------|
| <b>Benzyl alcohol</b>                            | 100-51-6  | 25-50% |
| <b>3 Amino methyl trimethylcyclo hexyl amine</b> | 2855-13-2 | 10-25% |
| <b>Salicylic acid</b>                            | 69-72-7   | 1-10%  |
|  |           |        |
| <b>Benzyl alcohol</b>                            | 100-51-6  | 25-50% |
| <b>3 Amino methyl trimethylcyclo hexyl amine</b> | 2855-13-2 | 10-25% |
| <b>Salicylic acid</b>                            | 69-72-7   | 1-10%  |
| <b>1-10</b>                                      |           | 100%   |

#### 4. FIRST AID MEASURES

If Poisoning occurs, contact a doctor or poisons information Centre (Phone Australia 131 126, New Zealand 0800 764 766)

##### Inhalation

Remove victim from exposure- avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing labored and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

##### Skin contact

For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering or irritation occurs seek medical assistance. A component of this material can be absorbed through the skin with resultant toxic effects. Seek medical advice.

##### Eye contact

If in eyes wash out immediately with large amount of water. Seek medical attention.

##### Ingestion

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting happens give further water. Seek immediate medical advice.

## Proudly Australian Made

### PPE for First aiders

Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapor/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

### Medical attention

Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

### Extinguishing media

#### Suitable extinguishing equipment

Alcohol resistance foam is the preferred fire-fighting medium. If material is involved in the fire use alcohol resistance foam, standard foam or Dry agent (Dry Chemical Powder, CO<sub>2</sub>).

### Specific Hazards

Flammable liquid. May form flammable vapor mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapor may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flame, pilot lights, furnaces, spark producing, switches and electrical equipment etc.) must be eliminated both in and near the work area. Do NOT smoke.

### Firefighting further advice

Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path to fire. Keep containers cool with water spray. On burning, may emit toxic fumes, including oxides of carbon and nitrogen. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapor or products of combustion.

### Special protective equipment and precautions for fire fighters

Wear breathing apparatus when fighting fire.

Hazchem Code: +3[Y]

## 6. ACCIDENTAL RELEASE MEASURES

## Proudly Australian Made

### Minor spill

Extinguish naked flames. And avoid sparks. Wear protective equipment to prevent skin and eye contamination. Wipe out with absorbent (clean rag or paper towel) or absorb with sand, sawdust or earth. Collect in drums, and arrange for disposal by a competent contractor, in accordance with local regulations.

### Major spill

Shut off possible source of ignition. Clear area of all unprotected personal. Prevent further leakage or spillage if safe to do so. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapors. Work up wind or increase ventilation. Contain – prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. Use a spark-free shovel. Arrange disposal by competent contractor, in accordance with local regulations. If contamination of sewers or waterways has occurred advice local emergency services.

### Dangerous Goods – Initial Emergency Response Guide No: 14

## 7. HANDLING AND STORAGE

### Precaution for safe handling

This product is flammable. Avoid sources of heat, naked flames and sparks. Use in well-ventilated area. Use flame proof equipment. No smoking. Earth all containers to reduce the possibility of sparks from static electricity. Avoid skin and eye contact and inhalation of vapor, mist or aerosols.

### Conditions for safe storage

Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuff. Store away from incompatible materials described in section 10. Store away from source of heat or ignition. Keep container closed when not in use - check regularly for leaks.

This material has classified as **Dangerous Good Class 3 Flammable Liquid** as per criteria of the Australian Dangerous Code and must be stored in accordance with the relevant regulations.

This material is a Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

| Chemical Entity | TWA <sup>1</sup> |                   | STEL <sup>2</sup> |                   |
|-----------------|------------------|-------------------|-------------------|-------------------|
|                 | ppm              | mg/m <sup>3</sup> | ppm               | mg/m <sup>3</sup> |
|                 |                  |                   |                   |                   |

## Proudly Australian Made

|   |     |     |
|---|-----|-----|
| <b>Benzyl Alcohol</b>                           | N/A | N/A |
| <b>3 Aminomethyl trimethyl cyclohexyl amine</b> | N/A | N/A |
| <b>Salicylic Acid</b>                           | N/A | N/A |
|   |     |     |

<sup>1</sup> Time weighted average concentration

<sup>2</sup> Short-term exposure limit

These exposure standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentration of chemicals. They are not a measure of relative toxicity. If the direction for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers routinely, potentially exposed during product manufacture.

### Biological Limit Values

As per the “National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)” the ingredients in this material do not have a Biological Limit Allocated.

### Engineering controls

Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use with local exhaust ventilation or while wearing appropriate respirator. Ventilation equipment should be explosion proof. Vapor heavier than air-prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapor may have collected. Keep containers closed when not in use.

### Exposure Controls

#### Personal protective equipment

G: OVERALL, SAFETY SHOES, SAFETY GLASSES, GLOVES, RESPIRATOR.

Wear overalls, chemical safety glasses/goggles and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapor/ particular respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

#### Hygiene Measures

Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid skin and eye contact and inhalation of vapor, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

Proudly Australian Made

## 9. PHYSICAL AND CHEMICAL PROPERTIES

| Property                 | Unit of measurement | Typical value                                    |
|--------------------------|---------------------|--|
| Appearance               | -                   | Coloured, Viscous Liquid                         |
| Odour                    | -                   | Mild odour                                       |
| Solubility               | -                   | Soluble in organic solvent<br>Insoluble in water |
| Vapor Pressure @ 25°C    | hPa                 | 0.03hPa  |
| Boiling Point            | °C                  | >260C  |
| % Volatile by Volume     | %                   | 0  |
| Melting Point/Range      | °C                  | Not available                                    |
| Autoignition Temperature | °C                  | Not available                                    |
| Decomposition Point      | °C                  | Not available                                    |
| Flash Point              | °C                  | 252  |
| Density @ 25°C           | g/ml                | 1.0-1.10   |
| Flammability Limits      | %(v/v)              | N/A  |
| Volatile content         | %(w/w)              | 0  |

## 10. STABILITY AND REACTIVITY

### Reactivity

No reactivity hazards are known for the material.

### Chemical stability

This material is thermally stable when stored and used as directed.

### Conditions to avoid

Elevated temperature, Source of heat and ignition, open flames.

### Incompatible materials

Incompatible with oxidizing agents.

### Hazardous decomposition products

Oxides of carbon and nitrogen, smoke and other toxic fumes.

Proudly Australian Made

## Hazardous reactions

No Known hazardous reaction.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may rise if the product is mishandled and overexposure occurs are:

### Acute effects

#### Ingestion

Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is uncoordinated there is greater likelihood of vomit entering the lung and causing subsequent complications.

#### Eye Contact

May be an eye irritant.

#### Skin Contact

Contact with skin will result in irritation. A component of this material can be absorbed through the skin. Effects can include those described for "INGESTION".

#### Inhalation

Material may be an irritant to mucous membranes and respiratory tract. Inhalation of vapor can result in headaches, dizziness and possible nausea. In halation of high concentration can produce central nervous system depression, which can lead to loss of coordination, impaired judgment and if exposure id prolonged, unconsciousness.

### Acute toxicity

#### Inhalation

This material has been classified as a Category 4 Hazard.  
Acute toxicity estimate (based on ingredients): 10-20 mg/L.

#### Skin contact

This material has been classified as a Category 4 Hazard.  
Acute toxicity estimate (based on ingredients): 1000-2000 mg/L.

#### Ingestion

This material has been classified as non-hazardous.



## Proudly Australian Made

### **Corrosion/irritancy**

Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as a Category 2 Hazard (irritant to skin).

### **Sensitization**

Inhalation: this material has been classified as not a respiratory sensitizer. Skin: this material has been classified as a skin sensitizer.

### **Aspiration hazard**

This material has been classified as non-hazardous.

### **Specific target organ toxicity (single exposure)**

This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in depression of the central nervous system.

### **Chronic toxicity**

### **Mutagenicity**

This material has been classified as non-hazardous.

### **Carcinogenicity**

This material has been classified as non-hazardous.

### **Reproductive toxicity**

This material has been classified as a non-hazardous.

### **Specific target organ toxicity (repeated exposure)**

This material has been classified as a non-hazardous.

## **12. ECOLOGICAL INFORMATION**

Avoid contaminating waterways.

### **Acute aquatic hazard**

This material has been classified as a Category Acute 1 Hazard.  
Acute toxicity estimate (based on ingredients) :<1 mg/L

## Proudly Australian Made

### Long-term aquatic hazard

No information is available to complete an assessment.

### Ecotoxicity

No information is available to complete an assessment.

### Persistence and degradability

No information is available.

### Bioaccumulation potential

No information is available.

### Mobility

No information is available.

## 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see “Section 8. Exposure Controls and Personal Protection” of this SDS.

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Advise flammable nature.

If possible material and container should be recycled. If material and container cannot be recycled, dispose in accordance with local, regional, national and international regulations.

## 14. TRANSPORT INFORMATION

### Road and Rail Transport

Classified as Dangerous Goods by criteria of the “Australian Code for the Transport of Dangerous Goods by Road and Rail” and the “New Zealand NZS5433: Transport of Dangerous Goods on Land”.

|                      |                |
|----------------------|----------------|
| UN No.               | 3082           |
| Proper Shipping Name | AMINES         |
| DG Class             | 8 Corrosive    |
| Subsidiary Risk      | Not Applicable |
| Packing Group        | III            |

## Proudly Australian Made

|                                  |   |
|----------------------------------|---|
| Hazchem Code                     | 8 |
| Initial Emergency Response Guide |   |

Segregation Dangerous Goods: Not to be loaded with explosive (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidizing agents (Class 5.1), organic peroxides (Class 5.2) or radioactive substances (Class 7), however exemptions may apply.

### Marine Transport

Classified as Dangerous Goods by the criteria of the international Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.

|                      |             |
|----------------------|-------------|
| UN No.               | 2735        |
| Proper Shipping Name | amines      |
| DG Class             | 8 corrosive |
| Packing Group        | III         |

### Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

|                      |             |
|----------------------|-------------|
| UN No.               | 2735        |
| Proper Shipping Name | AMINES      |
| DG Class             | 8 corrosive |
| Packing Group        | III         |

## 15. REGULATORY INFORMATION

### This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)  
The Stockholm Convention (Persist Organic Pollutants)  
The Rotterdam Convention (Prior Informed Consent)

### This material is subject to the following international agreements:

Basel Convention (Hazardous waste)

- Waste from production, formulation and use of inks, dyes, pigments, paints, lacquers, varnish.
- International convention for the prevention of pollution from ships (MARPOL)
- Annex III- Harmful substances carried in package form

## Proudly Australian Made

### This material/constituent(s) is covered by the following requirements:

- All the constituents of this material are listed on the *Australian Inventory of Chemical Substances (AICS)*.

## 16. OTHER INFORMATION

**Reason for Revision:** Information updates of all sections to comply with *Code of Practice Safe Work Australia, December 2011*.

### **Abbreviations:**

ADG: Australian Code for the Transport of Dangerous Goods by Road and Rail

CAS Number: Chemical Abstracts Number

HMIS: Hazardous Materials Identification System

TWA: the time-weighted average airborne concentration over an eight-hour working day, for five-day working week over an entire working life.

STEL: short term exposure limit, the average airborne concentration over a 15-minute period which should not be exceeded at any time during a normal eight-hour work day.

### **Disclaimer**

*Data provided is to best of Omega Paint knowledge and believe to be accurate and reliable as of the date of issued. However, no expressed or implied warranties are given. Omega Paint cannot anticipate or control the conditions under which this information may be used. Therefore, it is user's responsibility to satisfy themselves as to the suitability and completeness of such information for their particular use. It is the responsibility of the user to ensure that the issue is current. This information given is a non-controlled document.*