



PREMIUM PAINT

Australian Made & Australian Owned



Enamel Thinner

Production Description

Enamel Thinner is a blend of quick evaporating solvent specially formulated for quick dry enamels, primers and Hammertone.

Areas of Application

Can be used as thinner for Quick Dry Enamels, Zinc Phosphate Primers and Hammertone.

Technical Data

Appearance	Low viscosity, colourless clear liquid
Specific Gravity	0.79
Boiling Range	99-130 °C
Thinning Recommendations	Added to Alkyd coatings For spraying 10 – 30% is required. Refer individual product data sheet for specific recommendations.
Packs available	1 litre, 4 litre, 10 litre, 20 litre, 60 litre & 200 litre

Flammability & Transport

- Highly flammable, Dangerous Goods Class 3.2.
- Keep away from heat and flame, eliminate any source of ignition.
- Soak all used cloths and rags immediately in water to prevent self-ignition.
- Ensure container is upright with lid secure.
- Ensure the container is secured in the vehicle for transport.

Safety & Precautions

Refer to SDS for detail instructions.

The technical information and suggestions for use and application are given in good faith. Since conditions of use are beyond the manufacturer's control, information contained herein is without warranty, implied or otherwise. The manufacturer does not assume any liability for any loss or injury resulting from the use of the product. Cooler temperature, higher film thickness and higher humidity conditions will require longer drying times

Omega Paints Pty Ltd., 13-27 Melbourne Road Riverstone NSW 2765 Phone (02) 9832 0000 /

info@omegapaints.com.au

Reviewed Nov 2018